



SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017

ELEMENT MATERIALS TECHNOLOGY MINNEAPOLIS LLC  
(A subsidiary of Element Materials Technology Minneapolis Inc.)  
9725 Girard Avenue South  
Minneapolis, MN 55431 2621  
513-571-1176

Sandra Frank E-mail: [sandra.frank@element.com](mailto:sandra.frank@element.com)

MECHANICAL

Valid to: August 31, 2023

Certificate Number: 1719.01

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory for the following environmental simulation and mechanical tests on the following products and materials: aircraft components, automotive components, gaskets, seals and packings, packaging and containers, pipes, hoses, valves and fittings, rubber and rubber products, tools, windows and doors, wiring harnesses, subassemblies, telecommunication cabinets and components in the Telecommunications, Aircraft, Aerospace, Automotive, Medical, Defense, Electronics and Agriculture industries.

**Test Technology/Description:**

**Test Method(s)/Standard(s)<sup>3</sup>:**

Compression

ASTM D642;  
GR-3125-CORE;  
GR-3121-CORE;  
GR-3120-CORE;  
GR-487-CORE;  
GR-771-CORE;  
GR-950-CORE;  
GR-3178-CORE

Explosion

MIL-STD-810, Method 511;  
RTCA/DO-160, Section 9;  
ISO 8846

Earthquake / Seismic<sup>1</sup>  
*Frequency: (1 to 500) Hz*  
*Velocity: 40 in/sec*  
*Displacement: 10.5 in*

GR-63-CORE;  
ICC-ES AC 156;  
GR-3121-CORE;  
GR-3123-CORE;  
GR-3125-CORE;  
GR-13-CORE;  
GR-487-CORE;  
GR-950-CORE;  
GR-3108-CORE;  
GR-3178-CORE

A handwritten signature in blue ink, appearing to be 'Sandra Frank', is located in the bottom right area of the page.

**Test Technology/Description:**

**Test Method(s)/Standard(s)<sup>3</sup>:**

Firearms Resistance<sup>2</sup>

GR-487-CORE;  
GR-3125-CORE;  
GR-13-CORE;  
GR-771-CORE;  
GR-937-CORE;  
GR-950-CORE;  
GR-3108-CORE;  
GR-3178-CORE

Fire Test / Flammability

DOT/FAA AC 20-135;  
ISO 2685;  
RTCA/DO-160, Section 26;  
SAE AS4273;  
SAE AS1055;  
UL 94;  
GR-13-CORE;  
GR-63-CORE;  
GR-487-CORE;  
ANSI T1-319;  
GR-3120-CORE;  
GR-3125-CORE;  
GR-771-CORE;  
GR-937-CORE;  
GR-950-CORE;  
GR-3178-CORE;  
GR-326-CORE

Fungus

ASTM C1338;  
ASTM D3273;  
ASTM G21;  
GR-13-CORE;  
GR-487-CORE;  
MIL-STD-810, Method 508;  
RTCA/DO-160, Section 13;  
SAE J1455;  
GR-771-CORE;  
GR-950-CORE;  
MIL-PRF-28800 F;  
ASTM D2020

Hosedown / Water Resistance /  
Waterproofness / Enclosure Protection

IEC 60529, IPX3, Section 14.2.3;  
IEC 60529, IPX4, Section 14.2.4;  
IEC 60529, IPX5, Section 14.2.5;  
IEC 60529, IPX6, Section 14.2.6;  
IEC 60529, IPX7, Section 14.2.7;  
IEC 60529, IPX8, Section 14.2.8;  
NEMA 250 (2014);  
RTCA/DO-160, Section 10;  
UL 50 (2007);  
UL 50E (2007);  
MIL-STD-810, Method 512 (Immersion);  
GR-3125-CORE;



**Test Technology/Description:**

**Test Method(s)/Standard(s)<sup>3</sup>:**

Hosedown / Water Resistance /  
Waterproofness / Enclosure Protection  
(cont.)

GR-13-CORE;  
GR-487-CORE;  
GR-771-CORE;  
GR-937-CORE;  
GR-950-CORE;  
GR-3108-CORE;  
GR-3178-CORE

Humidity<sup>1</sup>  
*Up to 98% RH*  
*Temperature: (40 to 200) °F*

GR-487-CORE;  
GR-63-CORE;  
MIL-STD-810, Method 507;  
RTCA/DO-160, Section 6;  
SAE J1455;  
IEC 60945, Section 8.3;  
IEC 60068-2-30;  
IEC 60068-2-38;  
IEC 60068-2-56;  
IEC 60068-2-61;  
IEC 60068-2-78;  
IEC 60068-3-4;  
ASTM D4332;  
GR-3120-CORE;  
GR-3121-CORE;  
GR-3123-CORE;  
GR-3125-CORE;  
GR-13-CORE;  
GR-771-CORE;  
GR-937-CORE;  
GR-950-CORE;  
GR-3108-CORE;  
GR-3178-CORE;  
GR-326-CORE

Impact Resistance

ASTM D2794;  
GR-487-CORE;  
GR-3120-CORE;  
GR-3121-CORE;  
GR-3123-CORE;  
GR-3125-CORE;  
GR-13-CORE;  
GR-771-CORE;  
GR-937-CORE;  
GR-950-CORE;  
GR-3178-CORE;  
GR-326-CORE

Package Testing

ASTM D4169;  
GR-3120-CORE;  
GR-3121-CORE;  
GR-3123-CORE;  
GR-3125-CORE;  
GR-13-CORE



**Test Technology/Description:**

**Test Method(s)/Standard(s)<sup>3</sup>:**

Package Testing (*cont.*)

GR-487-CORE;  
GR-771-CORE;  
GR-950-CORE;  
GR-3108-CORE;  
GR-3178-CORE;  
GR-326-CORE

Salt Spray and Corrosion Resistance<sup>1</sup>  
*8'H x 8'W x 12'L Chamber*  
*Temperature: (30 to 55) °C*

ASTM B117; ASTM G85;  
GR-487-CORE;  
MIL-STD-810, Method 509;  
NEMA 250 (2014);  
RTCA/DO-160, Section 14;  
SAE J1455;  
UL 50 (2007); UL 50E (2007);  
IEC 60068-2-11;  
IEC 60945, Section 8.12;  
GR-3121-CORE;  
GR-3125-CORE;  
GR-13-CORE;  
GR-771-CORE;  
GR-937-CORE;  
GR-950-CORE;  
GR-3108-CORE;  
GR-3178-CORE;  
GR-326-CORE

Cyclic Corrosion Testing<sup>1</sup>  
*Temperature: (30 to 55) °C*

IEC 60945, Section 8.12;  
IEC 60068-2-52

Rain / Blowing Rain / Wind Driven Rain<sup>1</sup>  
*Velocity: up to 90 mph*  
*Rainfall Rate: up to 6 in/hr*

GR-487-CORE;  
MIL-STD-810, Method 506;  
NEMA 250 (2014);  
UL 497, Para. 34;  
UL 50 (2007);  
UL 50E (2007);  
IEC 60945, Section 8.8;  
GR-3125-CORE;  
GR-771-CORE;  
GR-950-CORE;  
GR-3178-CORE;  
GR-326-CORE

Temperature Exposure /  
High or Low / Thermal Shock<sup>1</sup>  
*Temperature: (-100 to 650) °F*

GR-487-CORE;  
GR-63-CORE;  
MIL-STD-810, Methods 501 and 502;  
NEMA 250 (2014);  
RTCA/DO-160, Section 4;  
SAE J1455;  
IEC 60945, Sections 8.2 and 8.4;  
IEC 60068-2-1;  
IEC 60068-2-2;  
IEC 60068-2-14;

**Test Technology/Description:**

**Test Method(s)/Standard(s)<sup>3</sup>:**

Temperature Exposure /  
High or Low / Thermal Shock<sup>1</sup>  
*Temperature: (-100 to 650) °F  
(cont.)*

IEC 60068-2-53;  
IEC 60068-2-61;  
GR-3120-CORE;  
GR-3121-CORE;  
GR-3123-CORE;  
GR-3125-CORE;  
GR-13-CORE;  
GR-771-CORE;  
GR-937-CORE;  
GR-950-CORE;  
GR-3108-CORE;  
GR-3178-CORE;  
GR-326-CORE

Temperature Shock<sup>1</sup>  
*Temperature: (-150 to 350) °F*

SAE J1455;  
MIL-STD-810, Method 503;  
IEC 60945;  
ASTM D4332;  
GR-13-CORE;  
GR-63-CORE;  
GR-487-CORE;  
GR-950-CORE

Tensile

ASTM D638;  
GR-326-CORE;  
GR-3120-CORE

Ultraviolet Resistance

ASTM D4459;  
ASTM G53-1996;  
ASTM G151;  
ASTM G154;  
ASTM G155;  
GR-487-CORE;  
IEC 60945, Section 8.10;  
IEC 60068-2-5;  
SAE J2527;  
UL 746C;  
UL 1581;  
MIL-STD-810, Method 505

Altitude / Pressure / Decompression<sup>1</sup>  
*(-2,000 to 120,000) ft*

GR-63-CORE;  
MIL-STD-810, Method 500, Procedures I, II, III, IV;  
RTCA/DO-160, Section 4;  
SAE J1455;  
IEC 60068-2-13;  
IEC 60068-2-40;  
IEC 60068-2-41;  
UL 50 (2007);  
UL 50E (2007);  
ASTM D6653;  
GR-3108-CORE

**Test Technology/Description:**

**Test Method(s)/Standard(s):**

Combined Environment (*excluding vibration*)

MIL-STD-810, Method 520

Sand and Dust

GR-487-CORE;  
IEC 60529, IP5X, Sections 13.4 and 13.5;  
IEC 60529, IP6X, Sections 13.4 and 13.6;  
RTCA/DO-160, Section 12;  
MIL-STD-810, Method 510;  
MIL-STD-202, Method 110;  
IEC 60068-2-68;  
GR-326-CORE;  
GR-937-CORE;  
GR-950-CORE;  
GR-3120-CORE;  
GR-3123-CORE;  
GR-3125-CORE

Highly Accelerated Life Testing (HALT)<sup>1</sup>

HALT and HASS (Section 3), Gregg K. Hobbs, Ph.D., PE; Hobbs Engineering; 1992. *Accelerated Reliability Engineering: HALT and HASS* (pp. 31-75);

Highly Accelerated Stress Screening (HASS)<sup>1</sup>

*Temperature: (-100 to 200) °C*  
*Ramp Rate: 70 °C/min*  
*50 Grms Repetitive Shock with Six*  
*Degrees of Freedom*

*HALT, HASS & HASA Explained: Accelerated Reliability Techniques* (pp. 2-25) Harry W. McLean, ASQ Quarterly Press, 2000

Shock / Drop

GR-487-CORE;  
GR-63-CORE;  
MIL-STD-810, Method 516;  
RTCA/DO-160, Section 7;  
SAE J1455;  
IEC 60945, Section 8.6;  
IEC 60068-2-27;  
IEC 60068-2-31;  
ASTM D5276;  
GR-3121-CORE;  
GR-3123-CORE

Vibration, Standard / Transportation<sup>1</sup>

*(1 to 3,000) Hz @*  
*18,000 lbf Sine or*  
*15,000 lbf Random*

GR-487-CORE;  
GR-63-CORE;  
MIL-STD-810, Method 514;  
RTCA/DO-160, Section 8;  
SAE J1455;  
IEC 60945, Section 8.7;  
IEC 60068-2-6;  
IEC 60068-2-50;  
IEC 60068-2-51;  
IEC 60068-2-53;  
IEC 60068-2-64;  
IEC 60079-29-1, Section 5.4.13;  
IEC 60079-29-4, Section 5.4.8;  
ASTM D4728;  
ASTM D999;  
MIL-STD-167;



**Test Technology/Description:**

**Test Method(s)/Standard(s):**

Vibration, Standard / Transportation<sup>1</sup>  
*(1 to 3,000) Hz @  
18,000 lbf Sine or  
15,000 lbf Random  
(cont.)*

GR-326-CORE;  
GR-3120-CORE;  
GR-3121-CORE;  
GR-3123-CORE;  
GR-3125-CORE

Acceleration<sup>1</sup>  
*Range: (0 to 110) Gs*

MIL-STD-810, Method 513, Procedures I and II;  
RTCA/DO-160, Section 7;  
IEC 60068-2-7

Icing / Freezing Rain

MIL-STD-810, Method 521;  
NEMA 250 (2014);  
RTCA/DO-160, Section 24;  
UL 50 (2007);  
UL 50E (2007);  
GR-487-CORE;  
GR-771-CORE;  
GR-950-CORE;  
GR-3120-CORE;  
GR-3125-CORE

Fluid Susceptibility / Immersion and Splash /  
Contamination by Fluids

MIL-STD-810, Method 504;  
RTCA/DO-160, Section 11;  
SAE J1455;  
IEC 60945, Sections 8.8, 8.9, and 8.11;  
IEC 60068-2-18;  
GR-487-CORE;  
GR-13-CORE;  
GR-771-CORE;  
GR-902-CORE;  
GR-937-CORE;  
GR-950-CORE;  
GR-3120-CORE;  
GR-3121-CORE;  
GR-3123-CORE;  
GR-3125-CORE

Acoustic Noise

GR-63-CORE;  
GR-487-CORE;  
GR-3108-CORE

Steam Cleaning / Pressure Washing

SAE J1455

**Telecommunications Tests:**

CATV Mechanical Bend and Torque	ANSI/SCTE 09; ANSI/SCTE 10; ANSI/SCTE 88; ANSI/SCTE 98; ANSI/SCTE 149; ANSI/SCTE 166
CATV Dimensional Measurements	ANSI/SCTE 31; ANSI/SCTE 33; ANSI/SCTE 39; ANSI/SCTE 51
CATV Tensile and Compression	ANSI/SCTE 59; ANSI/SCTE 61; ANSI/SCTE 73; ANSI/SCTE 99; ANSI/SCTE 191
CATV Environments	ANSI/SCTE 60; ANSI/SCTE 69; ANSI/SCTE 143

Industries served: Telecommunications, Aerospace, Defense, and Electronics

Note: This lab is capable of performing current and older versions of MIL-STD-810 (versions B through G) and RTCA/DO-160 (versions B through G) for the methods listed above. The methods listed above on this Scope are accredited. The following test method is a guideline utilized to perform the above fungus test: ***MIL-HBK-454B, Guideline 4.***

<sup>1</sup>Also using customer specific test methods utilizing any combination of test equipment parameters listed above.

<sup>2</sup>This laboratory performs field testing activities for these tests.

<sup>3</sup>When the date, edition, version, etc. is not identified in the scope of accreditation, laboratories may use the version that immediately precedes the current version for a period of one year from the date of publication of the standard measurement method, per part C., Section 1 of A2LA R101 - *General Requirements-Accreditation of ISO-IEC 17025 Laboratories.*