



SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017

ELEMENT MATERIALS TECHNOLOGY DETROIT - WARREN 11 MILE
27485 George Merrelli Drive
Warren, MI 48092

Stephen Karrer Phone: 586 754 9000 ext. 32900
Email: stephen.karrer@element.com

MECHANICAL

Valid To: December 31, 2024

Certificate Number: 0098.11

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory at the location above as well as the two satellite laboratory locations listed below to perform the following types of tests:

Mechanical Tests: Tensile/Elongation; Hardness (Durometer and Rockwell); Compression; Impact (Izod, Charpy, and GM9300P); Strength at Room and High Temperatures; Shear Strength; Physical Properties Following Fluid Exposure; Hoses and Tubing; Tear Strength Using Tongue, and Trapezoid Methods; Filler, Glass, Carbon Black Content; Volume Change; Specific Gravity and Density; Cleanability; Dimensional Stability; Water Absorption; Melt Flow/Index; Migration and Contact Staining; Flammability; Compression Set; Low-Temperature Brittleness; Deflection Temperature; On Plastics, Rubber, Elastomer, Composite, Paper/Paperboard, Construction Elements, and Textile Products.

Environmental Simulation Tests: Weatherometer (Xenon); Sunlamp and QUV Exposure; Fadometer; Ozone Resistance; Fogging; Salt Spray; CASS; Humidity; Condensing; Crocking; Water Immersion; Taber Abrasion; Gravelometer; Specular Gloss; Luminous Transmittance; Chromaticity; Color Reading; Corrodokote; Oil/Gas Immersion Solvent and Detergent Resistance; Thermal Shock; Paint Adhesion; Spot Test Acid/Water and Soap; Cleanability; Coating Thickness; Flexibility; Perspiration; Scrub Resistance; Dime Scrape; Cure Test; Thumbnail Hardness; Oven Aging; Scab Corrosion; Environmental Cycling; Accelerated Corrosion; Filiform Corrosion.

Environmental Chambers Testing: Temperature, Dust and Humidity Exposures are Performed during Durability Cycling Simulating Actual Environment; Microprocessors Control Chambers allowing Automatic Cycling and Tracking of Desired Time, Temperature and Humidity; Sizes up to 4m x 10m x 5m; Flow Measurement (Liquid and/or Gas): Hydraulic Pump Performance; Fan and Blower Delivery Capabilities, Radiator Heat Exchange Capacity, Heater Output; Stress Measurements; Pressure Testing; Durability Testing Mechanical/Electrical Cycling; Marine Products (Pumps/Motors/Electronics); Hydrostatic Leak Testing (up to 40,000 psi); Electrodynamics Vibration Systems: Generate Controlled Sine or Random Vibration, Sine-on Random Vibration Control, Transient Vibration Control, Mechanical Shock in Sawtooth, Half-sine and Squared Wave Forms, Field Data Replication, Operating or Non-Operating Mode Environments, High or Low Temperature and Humidity Conditions Can be Applied; Servohydraulic Test Systems: Control of Displacement, Force or Acceleration; Thermal Shock, Liquid and Air; Light Intensity; Sound; MAST, Pressure Cycling; Pressure-Vacuum Cycling; Temperature Cycling; Component Performance Testing; Performance Testing including Electrical Evaluation; Hydrostatic Burst Testing

Using the following capabilities:

(A2LA Cert. No. 0098.11 (Formerly 0038.01)) 3/22/2022

Page 1 of 16

<u>Test Technology</u>	<u>Range</u>	<u>Reference Standard</u>
Combined Environments:	(-77 to 177) °C; (20 to 95) % RH	MIL-STD-810 (Method 514 Procedure I)
Dimensional	(0.00015 to 36.000) in	WSS-M15P4
Force	(0.01 to 22,000) lbf	GMW3172
Humidity	(5 to 98) % RH	MIL-STD-810
Liquid Flow	0.01 cc/min to 35 gpm	GM10004C
MAST: Multi Axial Simulation Table ¹	(1 to 50) Hz 6 Degrees of Freedom +/- Three Axis in all Axis Linear Displacement 2.95 (+/-) Angular Displacement roll 6.8° Pitch and Yaw 8.5° Linear Acceleration at max payload Vertical: 5 g's, Lateral 3 g's, Longitudinal: 2.4 g's Max Payload 1000 lbs 4'x 6' to 6'x 8' Table Size	MAST USC.13324.200X 433132 (Per Customer Specification)
Pressure	(0.008 to 45,000) psi	ESDS7H-19B591-AA
Pulse Pressure	Up to 1000 PSIG, Up to 20 Hz	GMW14139
Servohydraulic Frequencies	Up to 50 Hz	MIL-STD-810 (Method 514 Procedure I)
Servohydraulic Load Capacity	Up to 150,000 lbf	MIL-STD-810 (Method 514 Procedure I)
Servohydraulic Stroke	Up to 50 inches	MIL-STD-810 (Method 514 Procedure I)
Temperature	(-100 to 650) °C	GMW14124
Torque	1 oz·in to 80,000 lbf·in	GMW15607
Vacuum	(0.008 to 29.98) in Hg	IEC 60068-2-13
Vibration:		
Displacement	2 in Peak to Peak	MIL-STD-810 (Method 514 Procedure I)
Load/Impact Velocity	1/2 SINE up to 1 ms to 35 m/s at Terminal Peak	MIL-STD-810 (Method 514 Procedure I)
Mechanical Shock Capacity	Up to 3,500 g	MIL-STD-810 (Method 514 Procedure I)
Vibration Acceleration	Up to 100 g	MIL-STD-810 (Method 514 Procedure I)
Vibration Frequencies	(3 to 2,700) Hz	MIL-STD-810 (Method 514 Procedure I)
Vibration Load Capacity	Up to 22,000 lbf	MIL-STD-810 (Method 514 Procedure I)

Also using customer specific test methods utilizing any combination of test equipment parameters listed above and the following tests and standards:



Test Method**Test Technology****Abrasion**

ASTM D4157
GMW15487
NES M0136 Method 1
SAE J948

Abrasion Resistance of Textiles, Wyzenbeek
Resistance to Abrasion of Organic Coating
Abrasion Resistance
Resistance to Abrasion

Martindale Abrasion

ASTM D4966
ASTM D4970

GMW3405
ISO 12945-2

ISO 12947-1
ISO 12947-2

ISO 12947-3
ISO 12947-4

Abrasion Resistance of Textile Fabrics
Pilling Resistance and Other Related Surface Changes of Textile
Fabrics: Martindale Tester
Seam Fatigue for Automobile Textiles
Determination of Fabric Propensity to Surface Fuzzing and to Pilling,
Modified Martindale Method
Abrasion Resistance of Fabrics by the Martindale Method
Abrasion Resistance of Fabrics by the Martindale Method – Specimen
Breakdown
Abrasion Resistance of Fabrics by the Martindale Method – Mass Loss
Abrasion Resistance of Fabrics by the Martindale Method –
Assessment of Appearance Change

Taber Abrasion

ASTM C501

ASTM D3389

ASTM D3884
ASTM D4060
FLTM BN 108-02
FLTM BN 108-04
SAE J1530
SAE J1847
SAE J365

Relative Resistance to Wear of Unglazed Ceramic Tile by the Taber
Abraser
Coated Fabrics Abrasion Resistance (Rotary Platform, Double-Head
Abrader)
Abrasion Resistance of Textiles, Taber
Taber Abrasion, Organic Coatings
Abrasion-Taber
Scuffing
Resistance to Abrasion, Bearding, and Fiber Loss of Carpet, Taber
Taber Abrasion
Scuffing Resistance, Taber

Adhesion

ASTM B571

ASTM D3359
ASTM D952
GMW14829
GMW14892

Qualitative Adhesion Testing of Metallic Coatings (Except Draw and
Push tests)
Adhesion Tape Test
Bond of Cohesive Strength of Sheet Plastics and Electrical Insulation
Tape Adhesion Test for Paint Finishes
Adhesion

Brittleness

Chrysler LP-463LB-11-01
Chrysler LP-463DD-07-01

Resistance to Cold Cracking of General Trim Materials

Charpy

ISO 179-1

Charpy Impact Properties, Non-Instrumented Impact Test



Test Method**Test Technology****Chemical Resistance**

AATCC TM 104	Spot Test Water
AATCC TM 15	Perspiration
AATCC TM 6	Spot Test Acid
ASTM D1308	Effect of Household Chemicals on Clear and Pigmented Organic Finishes
ASTM D4752	Measuring MEK Resistance of Ethyl Silicate (Inorganic) Zinc-Rich Primers by Solvent Rub
ASTM D1693	Environmental Stress Cracking
ASTM D471	Rubber Property-Effect of Liquids
ASTM D543	Resistance of Plastics to Chemical Reagents
ASTM D925 Method A	Staining of Surfaces (Contact/Migration/Diffusion)
ASTM F146	Fluid Resistance of Gasket Materials
Chrysler LP-463PB-31-01	Resistance to Various Fluids
Chrysler LP-463PB-57-03	Automotive Fluids Staining of Plastics
FLTM AN 101-01	Resistance of Textiles to Bleeding, Perspiration and Water Spotting
FLTM BI 113-01	Spot Test Water and Soap
FLTM BI 113-02	Spot Test Acid
FLTM BI 113-05	Acid Spotting of Painted Test Panels or Actual Finished Parts
FLTM BI 113-07	Resistance to Synthetic Perspiration Staining
FLTM BI 152-01	Resistance of Paint Films to Solvents
FLTM BN 103-01	Resistance of Coated Fabrics and Plastic Film to Migration Staining and Blocking
FLTM BN 112-08	Soiling & Cleanability Test for Interior Trim Materials
GMW14102	Determination of Water Spotting Test
GMW14141	Dye Migration
GMW14333	Fuel Resistance of Automotive Exterior Materials and Components
GMW14334	Chemical Resistance to Fluids
GMW14444	Material Related Interior Part Performance
GMW14445	Sunscreen and Insect Repellent Resistance
GMW14864	Procedure for Determining the Staining of Trim Materials Due to Sulfur Dioxide, SO ₂ , and Hydrogen Sulfide, H ₂ S
GMW14701	Resistance of Coatings to Chemical Etching and Distortion
GMW16625	Preparation of Acid Rain Solution
GMW3402	Soil and Cleaner Resistance of Automotive Materials
NES M0133 Method 2 & 3	Chemical Resistance Test Methods
Nissan 28401NDS01 [10] Section CH/11	Resistance to Calcium Chloride
<u>Color</u>	
ASTM D1003	Haze and Luminous Transmittance
ASTM D2244	Calculation of Color Differences from Instrumentally Measured Color Coordinates
SAE J1545	Delta-E Value (Color Measurement)



Test Method

Test Technology

Compression

ASTM D1056	Compression Force
ASTM D1229	Compression Set at Low Temperatures
ASTM D1621	Compressive Properties of Rigid Cellular Plastics
ASTM D395	Rubber Property-Compression Set (Method B)
ASTM D575	Rubber Properties in Compression
ASTM D695	Compressive Properties of Rigid Plastics
ASTM F36	Compressibility and Recovery of Gasket Materials
ISO 3386-2	Flexible Cellular Polymeric Materials – Determination of Stress-Strain Characteristics in Compression
ISO 815	Determination of Compression Set of Thermoplastic/Vulcanized Rubber at Ambient, Elevated, or Low Level Temperatures

Corrosion

ASTM B380	Corrosion Testing of Decorative Electrodeposited Coatings by the Corrodkote Procedure
FLTM BI 123-01	Painted Sheet Metal Corrosion, Apg
GMW14872	Cyclic Corrosion Chamber Humidity (20 to 100) %RH Chamber Temperature Ambient to 70°C Cycle Step Increments > 1 minute Atomized Solution Collection: Adjustable
GMW15282	Corrosion/Undercutting Scribe Creepback
GMW15288	Scab Corrosion Creepback of Paint Systems for Metal Substrates
SAE J2334	Cosmetic Corrosion

Salt Spray

ASTM B117	Operating Salt Spray (Fog) Apparatus
ASTM G85	Corrosion Testing
DIN 50021 (Withdrawn 06/88) ¹	Salt Spray (SS only)
GM4298P (Inactive 12/10) ²	Salt Spray Test
GMW3286	Neutral Salt Spray
ISO 9227	Corrosion Testing, Salt Spray
RTCA DO-160 Section 14.0	Environmental Conditions/Test Procedures for Airborne Equipment: Salt Spray

Crocking

AATCC TM 8	Crocking, Dry and Wet
FLTM BN 107-01	Crocking, Dry and Wet
SAE J861	Crocking



Test Method**Test Technology****Density**

ASTM D1622	Apparent Density of Rigid Cellular Plastics
ASTM D3776	Mass Per Unit Area (Weight) of Fabric
ASTM D792	Density Method A
GMW3182	Determination of Mass per Area
ISO 1183-1	Determining the Density of Non-Cellular Plastics Using Immersion Method
ISO 845	Cellular Plastics and Rubbers – Determination in Apparent Density (Bulk)

Dimensional

ASTM D1777	Thickness of Textile Materials
ASTM D5729	Standard Test Method for Thickness of Nonwoven Fabrics
ASTM D7091	Standard Practice for Nondestructive Measurement of Dry Film Thickness of Nonmagnetic Coatings Applied to Ferrous Metals and Nonmagnetic, Nonconductive Coatings Applied to Non-Ferrous Metals
FLTM BI 117-01	Coating Thickness
ISO 2808, Mtd 7C	Paints and Varnishes – Determination of Film Thickness
ISO 5084	Determination of Thickness of Textiles and Textile Products
SAE J882	Thickness of Textile Materials
SAE J883	Dimensional Stability of Automotive Textiles

Dynamic Mechanical Properties

ASTM D4065	Dynamic Mechanical Properties of Plastics
ASTM D4440	Rheological Measurements of Polymer Melts Using Dynamic Mechanical Procedures
ASTM D5279	Dynamic Mechanical Properties of Plastics Using Torsion
ISO 6721-1	Dynamic Mechanical Properties General Principles
ISO 6721-10	Dynamic Mechanical Properties Viscosity, Non-Resonance
ISO 6721-7	Dynamic Mechanical Properties Torsional, Non-Resonance

Environmental Exposure

Ford MA-0130	Humidity Aging
IEC 60068-2-78	Test Cab: Damp Heat, Steady State
ISO 22088-3	Determination of Resistance to Environmental Stress Cracking (ESC)
MIL-STD-810C/D/E/F/G (Sections 500-503, 507, 512-514, 516, 520, 524, 528 only)	Environmental Test Methods and Engineering Guidelines
NES M0153	Moisture Resistance Test Method
SAE J323	Cold Cracking of Flexible Plastic Materials



Test Method**Test Technology****Fabric, Leather, and Other Textiles**

ASTM D1117	Evaluating Non-woven Fabrics
ASTM D751	Coated Fabrics (except Bursting Strength, Hydrostatic Pressure, Adhesion Coating, Strength of Coating, Crack Resistance, and Crush Resistance)
FLTM BN 106-02	Seam Fatigue Testing
GMW3211	Resistance to Stretch and Set
ISO 13937-2	Tear Properties of Fabrics
SAE J913	Wicking
SAE J855	Stretch and Set

Fatigue

ASTM D6182	Flexibility and Adhesion of Finish on Leather
------------	---

Flexural

ASTM D747	Apparent Bending Modulus of Plastics by Means of a Cantilever Beam
ASTM D790	Flexural Properties of Unreinforced and Reinforced Plastics and Electrical Insulating Materials
ISO 178	Determination of Flexural Properties
SAE J949	Stiffness (Modulus of Bending)

Foams and Flexible Cellular Materials

ASTM D1667	Flexible Cellular Materials-Vinyl Chloride Polymers and Copolymers
ASTM D3574	Test Methods for Flexible Cellular Materials (except Test G, I4, Airflow, Test I2 Dynamic Fatigue Test by the Roller Shear at Constant Force, Test I4 Dynamic Fatigue Test for Carpet Cushion)
ASTM D3575	Test Methods for Flexible Cellular Materials Made from Olefin (except Sections 34-35, 45-46, 49-50, 66-67)

Fogging

GMW3235	Fogging
SAE J1756	Determination of Fogging Characteristics of Interior Automotive Materials
Toyota TSM0503G	Fogging Test Method for Non-Metallic Materials

Gloss

ASTM D523	Specular Gloss
FLTM BI 110-01	Specular Gloss
JIS Z 8741	Specular Glossiness Methods of Measurement

Hardness

ASTM D2240, Shore A and D	Durometer Hardness
ASTM D3363	Film Hardness by Pencil Test
ASTM D785 R Scale	Rockwell Hardness of Plastics and Electrical Insulating Materials
ISO 868	Plastic and Ebonite – Determination of Indentation Hardness by Means of a Durometer (Shore Hardness)

Test Method**Test Technology****Heat**

ASTM D2584	Ignition Loss of Cured Reinforced Resins
ASTM D3012	Thermal-Oxidative Stability of Propylene Plastics Using a Specimen Rotator Within an Oven
ASTM D3769	Heat Sag
ASTM D518	Rubber Deterioration-Surface Cracking
ASTM D573	Rubber-Deterioration in an Air Oven
ISO 188	Rubber, Vulcanized Thermoplastic-Accelerated Aging and Heat Resistance Test
ISO 3451-1	Determination of Ash
SAE J912	Blocking Resistance

Hoses and Hard/Soft Lines

ASTM D380	Method for Rubber Hose (except Sections 12-13)
GMW14319 Section 4.3.20 (pressure cycling) only	Air Conditioning Hose and Coupling Assemblies R134a and R1234yf
GMW14329 (Sections 4.3, 4.5, and 4.6)	Performance Testing of Heater and Coolant Hoses
GMW15724 (Section 4.3.8 (PDT) only)	Transmission and Engine Oil Cooler Plumbing System
PF 90080 (Sections 9.3.1 and 9.3.2 only)	Coolant Hoses and Plumbing Assemblies

Humidity & Water Resistance

ASTM D870	Testing Water Resistance of Coatings Using Water Immersion
ASTM D1735	Standard Practice for Testing Water Resistance of Coatings Using Water Fog Apparatus

Impact

ASTM D2137	Brittleness Point of Flexible Polymers and Coated Fabrics
ASTM D5420	Gardner Impact
ASTM D746	Brittleness Temperature of Plastics Elastomers by Impact
GMW16746	Evaluating Brittleness of Painted Plastics
SAE J400	Chip Resistance of Surface Coatings

Izod

ASTM D1822	Tensile Impact
ASTM D256	Izod Pendulum Impact Resistance of Plastics
ASTM D4812	Unnotched Cantilever Beam Impact Strength of Plastics
ISO 180	Plastics – Determination of Izod Impact Strength

Melt Flow

ASTM D1238	Melt Index (Flow Rate)
ISO 1133-1	Plastics – Determination of the Melt Mass-Flow Rate (MFR) and the Melt Volume-Flow Rate (MVR)

Test Method**Test Technology****Odor**

FLTM BO 131-03	Interior Odor Test
GMW3205	Test Method for Determining the Resistance to Odor Propagation of Interior Materials
GMW3259	Determination of Resistance to Mildew Growth
SAE J1351	Hot Odor Test for Insulation Materials
Toyota TSM0505G	Smell Quality of Non-Metallic Materials
VDA 270	Determination of the Odor Characteristics
VW PV3900	Odor Test

Ozone

ASTM D1149	Rubber Deterioration Surface Ozone Cracking in a Chamber (Method B only)
28400NDS26	Exposure Only

Peel

ASTM D1000	Unwind Pull (Method B only)
ASTM D3330	Peel Adhesion of Pressure Sensitive Tape
ASTM D413	Rubber Property-Adhesion to Flexible Substrate
ASTM D903	Peel or Stripping Strength of Adhesive Bonds
PSTC 101	Non-ASTM Peel

Permeability

ASTM D737	Air Permeability of Fabrics, Fraiser Method
ASTM E96	Water Vapor Transmissions

Protection against Dust, Sand, Water, or Foreign Object Ingress

DIN 40050-9 (Withdrawn 1993) ¹	Protection Against Foreign Objects; Water and Contact; Electrical Equipment (IP5KX, IP6KX, IPX1 through IPX4, IPX4K, IPX5, IPX6, IPX6K, IPX7, IPX8, IPX9K only)
IEC 60068-2-68	Dust and Sand (except LA1 and LC1)
IEC 60529	Degrees of protection provided by enclosures (IP code) (IP5X, IP6X, IPX1 through IPX9 only)
ISO 20653	Road Vehicles – Degrees of Protection (IP-Code) – Protection Against Foreign Objects, Water and Access – Electrical Equipment (IP5KX, IP6KX, IPX1 through IPX4, IPX4K, IPX5, IPX6, IPX6K, IPX7, IPX8, IPX9K only)
JIS D 0203 (R2, S1, S2)	Moisture, Rain and Spray Test for Automobile Parts
JIS D 0207	Dust Test for Automobile Parts (F-Type Only)

Scratch

FLTM BN 108-13	Scratch Test
GMW14130	Scuff and Mar Resistance
GMW14688	Resistance to Scratching
GMW14698 Method B	Scratch Resistance of Organic Coatings and Self-Adhesive Foils
Chrysler LP-463DD-18-01	Scratch and Mar Resistance of Automotive Plastics

Test Method

Test Technology

Tear

ASTM D1004
ASTM D2261
ASTM D5587
ASTM D5733
ASTM D624

Initial Tear Resistance of Plastic Film and Sheeting
Tongue Tear
Tearing Strength of Fabrics by the Trapezoid Procedure
Tearing Strength of Nonwoven Fabrics by the Trapezoid Procedure
Tear Strength of Conventional Vulcanized Rubber and Thermoplastic Elastomer
Tearing Strength of Textile Materials by Trapezoid Method
Fiber Degradation of Automotive Textiles
Determination of Tear Strength of Thermoplastic/Vulcanized Rubber Using Trouser, Angle and Crescent Pieces

GMW3326
GMW3387
ISO 34-1

Tensile

ASTM D1894
ASTM D3163
ASTM D412
ASTM D5034
ASTM D5035
ASTM D638
ASTM D882
ASTM E132
ASTM F152
ISO 1798

Static and Kinetic Coefficients of Friction of Plastic Film and Sheeting
Strength of Adhesive Bonded Rigid Lap Shear Joints
Tensile Properties, Vulcanized Rubber and Thermoplastics Elastomers
Tensile Strength
Breaking Strength, Textile Fabrics, Strip Method
Tensile Properties of Plastics (Including Poisson's Ratio)
Tensile Properties Thin Plastic Sheeting
Poisson's Ratio

ISO 37
ISO 527-1
ISO 527-2
ISO 527-3
ISO 527-4
ISO 527-5
ISO 8295
SAE J2044

Tension Testing of Nonmetallic Gasket Materials
Flexible Cellular Polymeric Materials- Determination of Tensile Strength and Elongation at Break
Determination of Tensile Stress/Strain Properties of Thermoplastic/Vulcanized Rubber
Tensile Properties Part 1 General Principles
Tensile Properties Part 2 Test Conditions for Molding and Extrusion Plastic
Tensile Properties Part 3 Film, Sheets
Tensile Properties Part 4 Isotropic and Orthotropic Fiber-Reinforced Plastics
Tensile Properties Part 5 Test Conditions for Unidirectional Fiber-Reinforced Plastics
Coefficient of Friction
Quick Connector Specification for Liquid Fuel and Vapor/Emissions Systems

Thermal Cycle

GMW14124
VW PV1200
Ford CETP 00.00.E-412
FCA CS.00056

Automotive Environmental Cycles
Resistance to Environmental Cycle Test (80 to -40) °C
Sections 6.4.5.1-6.4.5.8
Sections 5.3.1-5.3.7

Vibration

JIS D 1601

Vibration Testing Methods for Automobile Parts



Test Method

Test Technology

Vicat and HDT/DTUL

ASTM D1525	Vicat Softening Temperature of Plastic
ASTM D648	Deflection Temperature of Plastics Under Flexural Load in the Edgewise Position
ISO 306	Determination of Vicat Softening Temperature (VST) of Thermoplastic Materials
ISO 75-1	Plastics-Determination Temperature of Deflection Under Load Part 1 General Test Method
ISO 75-2	Plastics – Determination of Temperature of Deflection Under Load Part 2 Plastics and Ebonite
ISO 75-3	Plastics – Determination of Temperature of Deflection Under Load Part 3 High Strength Thermosetting

ELEMENT MATERIALS TECHNOLOGY³

14610 Jib Street
Plymouth, MI 48170

Test Method

Test Technology

Ford IP-0105	Instrument Panel Sunload Resistance
Ford MA-0128	Simulated Sunload Resistance – Exterior
Ford MA-0130	Humidity Aging
Ford MA-0131	Heat Age
Ford OR-0329	Sunload Resistance – Exterior Ornamentation
GMW14124	Automotive Environmental Cycles
NES M0132	Thermal Cycle Test Methods for Plastic Parts
Nissan 96030 NDS00	Air Spoiler Testing
PF-11084	Door Trim Panel Assembly and Components
WSS-M15P32-C	Trim Assembly, Enclosed Luggage Compartment Covering
WSS-M15P45-A (except 3.12)	Performance, Instrument Panel Assembly, Flexible Cover Skin Material
WSS-M15P4-E	Interior Trim, Assembly Performance
WSS-M15P4-F	Assembly Performance, Hard Mold-In-Color Interior Components
WSS-M15P4-G (Sections 3.4.1, 3.4.2, 3.5.1.1)	Assembly Performance, Hard Mold-In-Color Interior Components



ELEMENT MATERIALS TECHNOLOGY³
1920 Concept Dr.

Warren, MI 48091-1385

<u>Test(s):</u>	<u>Test Method(s):</u>
Abrasion Resistance Abrex	Ford FLTM BN 155-01; GS 97024-1, -4, -5; IEC 60068-2-70
Adhesion Testing	ASTM B571 (except sections 6 and 11), ASTM D3359; Ford BI 106-01, BI 106-02; GMW3368, GMW14829
Chip or Gravel Resistance	ASTM D3170; Ford BI 157-04, BI 157-06; GMW14700; Chrysler LP 463PB-52-01; SAE J400
Color Measurements Instrumental, sphere	ASTM D2244, ASTM E1331; SAE J1545, J1717 (Appendix E)
Visual (Light Booth)	SAE J1545; ASTM D1729; Ford BI 109-01; AATCC (EP1); ISO 105-A03
Corrosion Testing Spray (CASS) Testing	ASTM B368
Cyclic Corrosion Testing	Ford BQ 105-01, BI 123-01, BI 123-03, CETP 00.00-L-467; GMW14458, GMW14872, GMW15288; NES M0158-96 CCTI & CCTIV; SAE J2334
Environmental Conditioning & Cycling Cold Cycling	Chrysler LP-463DD-08-02
Humidity	ASTM D1735, ASTM D2247; GMW14729
Hot/ Cold/ Humidity Cycling	GM9310P; Chrysler LP-463DD-08-02
Hot/ Cold/ Humidity / IR	GMW15432
Accelerated Ageing/Automotive Cycles	ASTM D5427; GMW14124
Environmental Cycles / Exposure / Thermal Shock	Chrysler LP-463CB-10-01, LP-463LB-12-01, LP-463PB-22-01, LP-463PB-52-01, LP-463LB-13-01, LP-463PB-36-01; BI 107-05, BQ 104-07; DVO-0001-IP; GM9310, GMW14124, GMW14872, GMW15432; MIL-STD 810G (Methods 501, 502, 503, 507, 521)
Evaluations	ASTM D610, D660, D661, D714, D1654; Ford BI 160-01 (except procedure A); GMW15282
Falling Sand Abrasion	ASTM D968
Filiform Corrosion	ASTM D2803; Ford BI 124-01
Film Thickness	ASTM D7091; Ford BI 117-01;
Fluorescent UV Condensation Exposure	ASTM D4329, ASTM D4587, ASTM G151, ASTM G154; TSH3130G; SAE J2020
Fogging	GMW3235; HES D6508 SAE J1756; VW PV 3015 Chrysler LP-463DB-12-1; NES M0161; DIN 75201
Gloss/Haze Measurements	ASTM D523, ASTM D4039; Ford BI 110-01; SAE J1717 (Appendix E)



Test(s):

Test Method(s):

Hardness

Pencil

ASTM D3363

Humidity Resistance

Water Fog

ASTM D1735, ASTM D2247, ASTM D4585;

Condensing

Ford BI 104-02, BI 106-03, BQ 104-02;

Cleveland Condensing

GMW14729

Impact

Gardner

ASTM D2794, ASTM D5420 (Geometry GC and GE);

Ford BI 108-01,

BO 151-01 (Method B [Impact Ball Shore A 72.5])

Odor

NES M0160; TSM 0505G

PACCAR Paint Performance

PACCAR CMT-0033 (except section 8.1)

Salt Spray (Fog) Testing

ASTM B117, ASTM G85; ISO 9227; Ford BI 103-01;

GMW3286; NES M0140-01; JIS Z2371

Solvent Wipe

ASTM D5402; GMW15891

Standard Atmosphere for

ASTM D618; ISO 291

Conditioning & Testing

Three-Dimensional (3D) Image Blue-

Light Scanning

Scan Volume 200 mm x 150 mm
x 150 mm

ATOS V8 SR1 Manual Basic; Customer-Specified

Scan Volume 500 mm x 380 mm
x 380 mm

Water Resistance

Water Immersion

ASTM D870

Water Chemistry

Ford BI 104-01, BI 104-04

Car Wash

GMW16745, GMW17103

Weathering (Artificial)

Weatherometer

ASTM D2565

Xenon-Arc Exposure of Plastics Intended for Outdoor
Applications

ASTM D4459

Xenon-Arc Exposure of Plastics Intended for Indoor Applications

ASTM D7869

Xenon Arc Exposure Test with Enhanced Light and Water
Exposure for Transportation Coatings

ASTM G155

Operating Xenon Arc Light Apparatus for Exposure of Non-
Metallic Materials

Ford FLTM BO 116-01

Resistance to Interior Weathering

GMW14162

Colorfastness to Artificial Weathering

GMW3414

Colorfastness to Artificial Light

ISO 4892-2

Xenon Exposure Testing

SAE J1885 (Inactive 2008)¹

Accelerated Exposure of Automotive Interior Trim Components
Using a Controlled Irradiance Water Cool

SAE J1960 (Inactive 2008)¹

Xenon Arc Accelerated Exposure (External)

SAE J2412

Accelerated Exposure of Automotive Interior Trim Components
using a Controlled Irradiance Xenon-Arc

SAE J2527

Accelerated Exposure of Automotive Exterior Materials using a
Controlled Irradiance Xenon-Arc

Xenon Weathering utilizing any combination of the following parameters²:

(0.2 to 1.38) W/m ² at 340nm	Chamber Air Temperature (15 to 90) °C
(0.45 to 3.11) W/m ² at 420 nm	Black Panel Temperature (25 to 125) °C
(26 to 166) W/m ² at (300 to 400) nm	Chamber Humidity (10 to 95) %RH

<u>Test(s):</u>	<u>Test Method(s):</u>	<u>Parameter(s):</u>
------------------------	-------------------------------	-----------------------------

Flexible Test Cells

Durability Testing

Mechanical Cycling	DVM 0019-ST; GMW3067, GMW7699, GMW7000, GMW9123, GMW3172; Chrysler PF 8502, PF 8401, PF 11029; DC-10859, 10254; Customer Specifications ¹	Axial & Bending Fatigue: (50,000 lb max) Ultimate Strength: (200,000 lb max) Torsion: (up to 4000 ft./lbs – 100° Rotation) Pneumatic & Hydraulic actuation with force and/or position feedback
--------------------	---	--

Slosh	PF.90083; PF.8950	Table travel length up to 1250 mm Table weight capacity 1300 lbs Table speed up to 300 mm / second Table acceleration up to 1.0 g Table cycle rate up to 3 Hz
-------	-------------------	---

<u>Multi Axis Simulation Table (MAST)</u> (6 axis) up to 100 Hz	ST-0009; DC-10859 (Heidedauerlauf); IP-0008 (Key Life Test); Customer Specifications ²	6 DOF, vertical, lateral, longitudinal pitch, roll, and yaw inputs (-50 to 177) °C
--	---	---

Environmental Testing

Solar Loading/ Heating Testing	GM9310P; Chrysler PF 11084, 11029; Ford SDS IT 0005, 9014; MES PA 5500 D; NES MO 131;	Temperature: (-100 to 374) °F / (-73 to 190) °C (using various reach-in, walk-in, and drive-in chambers)
High & Low Temperature Testing with Relative Humidity Thermal Shock	Customer Specifications ²	Humidity: Up to 95% RH

Noise Analysis Testing

BSR Objective and Jury Evaluator	GMW7293, GMW14011; Customer Specifications ²	Real Time 33 db ambient
----------------------------------	--	-------------------------



Test(s):**Test Method(s):****Parameter(s):****Flexible Test Cells
(cont'd)**Vertical Pitch and Roll
+4D
Quiet Shaker SystemGMW14011, GMW14144,
GMW14155, GMW14188,
GMW14240, GMW14264,
GMW15655;
Chrysler LP.7R027, LP.7R0774,
PF 90192, PF 90052, PF 90223,
PF 90232 (2015), PF 90243,
PF 90283;
Ford CETP 00.00-L-448,
CETP 01.10-L-419_2,
CETP 01.12-L-300,
CETP 18.03-L-400,
CETP 00.00-E-412,
CETP 01.10-L-413,
CETP 12.00-L-403,
CES_Seat Recliner Component Eng.,
CES_Seat Track Component Eng.,
DVM-0010-SM,
ES-6E5H-19980-AJ, Seat SDS v18 or
newer

The laboratory is accredited for the test methods listed above. The accredited test methods are used in determining compliance with the material specifications listed below; however, the inclusion of these material specifications on this Scope does not confer laboratory accreditation to the material specifications. Inclusion of these material specifications on this Scope also does not confer accreditation for every method embedded within the specification. Only the methods listed above on this Scope are accredited.

Test(s):**Test Method(s):****Chrysler:**

CS-11982	Electrical/Electronic (E/E) Environmental Specification
MS JP 1-3	Color Durability of Interior Materials
MS-DC 40	Co-Extruded Polyethylene Film
PF-10952	Floor Console Assembly System Requirements
PF-11084	Door Trim Panel Assembly and Components
PF-11203	Material Durability Requirements for Interior Plastic Trim Components

Ford:

WSS-M1F27	Luxury Leather
WSS-M8P18	Fabric Performance
WSS-M15P32-C	Trim Assembly, Enclosed Luggage Compartment Covering



WSS-M15P45-A, Performance, Instrument Panel Assembly, Flexible Cover Skin Material
except section 3.12

Test(s): **Test Method(s):**

Ford (cont'd):

WSS-M15P4-E Interior Trim, Assembly Performance
WSS-M15P4-F Assembly Performance, Hard Mold-in-Color Interior Components
WSS-M15P4-G Assembly Performance, Hard Mold-In-Color Interior Components
WSS-M1F28 Leather
FMVSS 571.106 Brake Hoses

GM:

GMW14231 Automotive Fabrics
GMW14650 Performance Requirements for Exterior Plastic Parts
GMW16443 Peel Test Pressure Sensitive Adhesive
GMW15201 Double-Coated Foam Tape for Exterior Attachments
GMW14325 HVAC Air Ducts

Japan:

JIS L 1096 Woven Fabrics

Hyundai:

MS 300-32 Woven, Knit
MS 320-05 Fabrics for Seats

Nissan:

Nissan NES M0094 Flammability of Automotive Materials

SAE:

SAE J1639 Test Methods for Nylon Materials
SAE J17 Latex Foam Rubbers

Toyota:

Toyota TSH3130G Paint Quality for Interior Parts

Volkswagen:

VW PV3366 Elastomer Seals

¹ Using the following standards and test methods:

ASTM, FMVSS, JIS, ISO, IP, SAE, GM, Ford, Chrysler, Mazda, Honda, Toyota, Navistar, Paccar, Volvo, Freightliner, and standards and specifications furnished by the customer for the parameters listed above and the equipment capabilities.

² This laboratory's scope contains withdrawn or superseded methods. As a clarifier, this indicates that the applicable method itself has been withdrawn or is now considered "historical" and not that the laboratory's accreditation for the method has been withdrawn.

³ This accreditation covers the specified testing performed at the laboratory locations listed in this scope of accreditation.





Accredited Laboratory

A2LA has accredited

ELEMENT MATERIALS TECHNOLOGY DETROIT – WARREN 11 MILE

Warren, MI

for technical competence in the field of

Mechanical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 *General requirements for the competence of testing and calibration laboratories*. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).



Presented this 22nd day of March 2023.

A blue ink signature of Mr. Trace McInturff, written over a horizontal line.

Mr. Trace McInturff, Vice President, Accreditation Services
For the Accreditation Council
Certificate Number 0098.11
Valid to December 31, 2024

For the types of tests to which this accreditation applies, please refer to the laboratory's Mechanical Scope of Accreditation.