

SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017

ELEMENT MATERIALS TECHNOLOGY CANADA INC. Oakville Laboratory 2475 Speers Road Oakville, Ontario, Canada L6L 2X9 Luiz Rios Phone: 905-822-4111

THERMAL

Valid To: October 31, 2026

Certificate Number: 6524.03

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory for the following <u>fire tests</u>:

| Test Method: | Test Description: |
|--|--|
| 14 CFR Part 25 App. F, part I ¹ | Bunsen Burner Tests for Cabin Materials as cited in FAR 25.853(a), 25.855(a), 25.857(a), 29.853(a), 49 CFR Part 238 (Passenger Railcar Materials) and FTA Docket 90-A (Transit Bus and Van Materials) |
| 14 CFR Part 25 App F, part V ¹ | Smoke Generation of Aerospace Materials as cited in FAR 25.853(d) |
| 16 CFR 1610 ¹ | Commercial practices - standard for the flammability of clothing textiles |
| 16 CFR 1615 ¹ | Commercial practices - standard for the flammability of children's sleepwear: sizes 0 through 6X (FF 3-71) |
| 16 CFR 1632 ¹ | Commercial practices - standard for the flammability of mattresses and mattress pads (FF 4-72, amended) (supersedes California TB 106) |
| 16 CFR 1633 ¹ | Commercial practices - standard for the flammability (open flame) of mattress sets (supersedes California TB 603) |
| ASTM C1166 | Standard test method for flame propagation of dense and cellular elastomeric gaskets and accessories |
| ASTM D635 | Standard test method for rate of burning and/or extent and time of burning of plastics in a horizontal position |
| ASTM D1929 | Standard test method for determining ignition temperature of plastics |
| ASTM D2863 | Standard Test Method for Measuring the Minimum Oxygen Concentration to Support Candle-Like Combustion of Plastics. |
| ASTM D3675 | Standard test method for surface flammability of flexible cellular materials using a radiant heat energy source |
| ASTM D6413/D6413M | Standard test method for flame resistance of textiles (vertical test) |
| ASTM E84 | Standard test method for surface burning characteristics of building materials |
| ASTM E2768 | Standard Test Method for Extended Duration Surface Burning Characteristics of Building Materials (30 min Tunnel Test) |
| ASTM E136, Option A | Standard test method for behavior of materials in a vertical tube furnace at 750°C |

(A2LA Cert. No. 6524.03) 02/28/2025

Page 1 of 3

| Test Method: | Test Description: |
|---------------------------------------|---|
| ASTM E162 | standard test method for surface flammability of materials using a radiant heat energy source |
| ASTM E648 | Standard test method for critical radiant flux of floor-covering systems using a radiant heat energy source |
| ASTM E662 | Standard test method for specific optical density of smoke generated by solid materials |
| ASTM E970 | Standard test method for critical radiant flux of exposed attic floor insulation using a radiant heat energy source |
| ASTM E1353 (Withdrawn) | Standard test methods for cigarette ignition resistance of components of upholstered furniture |
| ASTM E1354 | Standard test method for heat and visible smoke release rates for materials and products using an oxygen consumption calorimeter |
| Bombardier SMP 800-C | Toxic gas generation of "suppress 5/8" sound engineering drywall" composite |
| Boeing BSS 7239 | Fire test to aircraft material – toxicity |
| California Administrative Code | Public Safety, Regulations Relating to Flame-retardant Chemicals, |
| Title 19 (para. 1237.1 and 1237.3) | Fabric and Application Concerns – Test Requirements for Exterior Flame-retardant Chemicals – Fire Resistance |
| California TB 117 | Requirements – test procedure and apparatus for testing the flame retardance of resilient filling materials used in upholstered furniture |
| CAN/CSGB 4.2 M 27.1 | Textile test methods - flame resistance - vertical burning test |
| CAN/CSGB 4.2 M 27.5 | Test Method for Flammability of Apparel Textiles |
| CAN/CSGB 4.2 M 27.7 | Textile test methods for combustion resistance of mattresses |
| CAN/CSGB 4.2 No. 27.10 | Textile test methods - flame resistance - vertically oriented textile fabric or fabric assembly test |
| CAN/ULC-S102 | Standard method of test for surface burning characteristics of building materials and assemblies |
| CAN/ULC-S102.2 | Method of test for surface burning characteristics of flooring, floor coverings, and miscellaneous materials and assemblies |
| CAN/ULC-S109 | Standard method for flame tests of flame resistant fabrics and films |
| CAN/ULC-S114 | Standard method of test for determination of non-combustibility in building materials |
| CAN/ULC-S127 | Standard corner wall method of test for flammability characteristics of non-melting building materials |
| CAN/ULC-S129 | Standard Method of Test for Smoulder Resistance of Insulation (Basket Method) |
| CAN/ULC-S135 | Standard method of test for determination of degrees of combustibility of building materials using an oxygen consumption calorimeter (cone calorimeter) |
| CAN/ULC-S137 | Standard method of test for fire growth of mattresses (open flame test) |
| CMVSS 302/FMVSS 302 | Flammability of interior materials test |
| CPAI 84 | Specification for flame-resistant materials used in camping tentage |
| ISO 871 | Plastics determination of ignition temperature using a hot-air furnace |
| ISO 5660-1 | Reaction-to-fire tests heat release, smoke production and mass loss rate part 1: heat release rate (cone calorimeter method) |
| NFPA 253 | Standard method of test for critical radiant flux of floor covering systems using a radiant heat energy source |

(A2LA Cert. No. 6524.03) 02/28/2025

hu

| Test Method: | Test Description: |
|--------------|--|
| NFPA 258 | Recommended practice for determining smoke generation of solid materials |
| NFPA 260 | Standard methods of tests and classification system for cigarette ignition resistance of components of upholstered furniture |
| NFPA 701 | Standard methods of fire tests for flame propagation of textiles and films |
| UFAC | Fire Tests, Components, Cigarette Ignition Mattresses |
| UL 94 | Standard for tests for flammability of plastic materials for parts in devices and appliances |
| UL 723 | Standard for test for surface burning characteristics of building materials |

¹The Consumer Product Safety Improvement Act (CPSIA) requires that every children's product subject to a federal consumer product safety requirement be tested by a Consumer Product Safety Commission (CPSC) accepted laboratory for compliance with the applicable federal children's product safety requirements. Accreditation by A2LA does not infer acceptance by the CPSC. Please verify this organization's acceptance status by using the CPSC's searchable database, located at http://www.cpsc.gov/cgi-bin/labsearch/.

(A2LA Cert. No. 6524.03) 02/28/2025

An



Accredited Laboratory

A2LA has accredited

ELEMENT MATERIALS TECHNOLOGY CANADA INC.

Oakville, Ontario, Canda

for technical competence in the field of

Thermal Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).



Presented this 28th day of February 2025.

Mr. Trace McInturff, Vice President, Accreditation Services For the Accreditation Council Certificate Number 6524.03 Valid to October 31, 2026

For the tests to which this accreditation applies, please refer to the laboratory's Thermal Scope of Accreditation.